


# IC-S 300

## INSPECTION CHAMBER



ArchiGreen Roof Ltd  
 3 Patzay Pal Utca • Gyor • H-9024  
 Website: [www.archigreenroof.com](http://www.archigreenroof.com)  
 E-mail: [info@archigreenroof.com](mailto:info@archigreenroof.com)

IC-S 300 is a 300 mm high lockable inspection chamber comprising four elements:

- A. The base, a square-shaped casing with an open underside, is made of UV-resistant polypropylene (PP).
- B. The lid, detachable, is made of PP.
- C. The filter grille is made of stainless steel.
- D. The lock, chrome-plated durable quarter turn lock, is made of zinc alloy.

The filter grille and the lock are integrated into the lid that is recessed into the base. The detachable lid has tread pattern on its surface to prevent slipping hazards.

Screws are made of stainless steel (Grade A2) and their fixing is in accordance with DIN7505.

IC-S stands on 4 load distribution footprints positioned at the corners.

### Use

Usage of the IC-S range include:


- Allowing for the inspection and maintenance of outlets
- Securing proper and continuous drainage of surface water
- Preventing contamination and direct sunlight into the outlets
- Restraining the recommended pebble vegetation barrier
- Stopping plants from growing over the outlet
- Serving as visual indicators for the locations of outlets present

### Application area

IC-S 300 inspection chamber is directly installed over each green / gravel roof outlet, set on the drainage layer within a surrounding build-up of 300 mm in depth.

Size (L x W x H)	300 x 300 x 300 mm
Weight	3.98 kg
Base and lid	Polypropylene (PP)
Colour	RAL 7032 - pebble grey
Filter grille	Stainless steel
Perforations of filter grille	German FLL Guidelines
Area of filter grille	2534 mm <sup>2</sup>
Effective drainage area	1300 mm <sup>2</sup>
Screws (Grade)	Stainless steel (A2)
Screws fixing standard	German Standard DIN 7505
Lock	Zinc alloy die casting
Finish of lock	Chrome-plated
Load distribution surface	22,106 mm <sup>2</sup>
Environmental aspect	Fully recyclable


### Installation example



### Specification suggestion

ArchiGreen® IC-S 300 lockable inspection chamber is made of UV-resistant polypropylene (PP), RAL colour 7032, with a stainless steel filter grille and a durable chrome-plated quarter turn lock made of zinc die casting alloy fitted into its detachable lid. Anti-slip tread pattern marks the surface of the lid. The grille allows for the inflow of surface water via 1300 mm<sup>2</sup> perforated area according to German FLL Guidelines. Size and weight including lid: 300 x 300 x 300 mm (L x W x H); 3.98 kg. Four separate load distribution footprints are fixed to the underside via stainless steel screws (Grade: A2). Fastener fixing standard: German Standard DIN 7505. Delivery and installation is in accordance with manufacturer's instructions.

### Technical illustration



### Tools required

No special tools are required for the installation of this product.

### Packaging unit

IC-S 300 can be despatched in corrugated boxes or on wooden pallets depending on the size of the order. 30 units of IC-S 300 being stretch wrapped would fit on a single EUR-pallet (1200x800 mm).